SPECIFICATIONS - FORTIS ClearView SMD

Core Specifications		
Pixel Pitch	1.9	2.9
Pixel Configuration	SMD + GOB*	SMD + GOB*
Module Size (mm) (ft'in") (W×H)	250 x 250 / 0' 9.84" × 0' 9.84"	250 x 250 / 0' 9.84" × 0' 9.84"
Module Resolution (pixels) (W×H)	128 x 128	128 x 128
Cabinet Size (mm) (ft'in") (W×H×D)	500 x 500 x 97 / 1' 7.69" × 1' 7.69" × 0' 3.82"	500 x 500 x 97 / 1' 7.69" × 1' 7.69" × 0' 3.82"
Cabinet Resolution (pixels) (W×H)	256 x 256	168 x 168
Display Size (mm) (ft'in") (W×H×D)	N/A	
Display Resolution (pixels) (WxH)	N/A	
Display Diagonal (in)	N/A	
Weight (kg/m²) (lbs/ft²)	N/A	
Cabinet Weight (kg/lbs)	31 / 68.3	31 / 68.3
Maintenance	Front & Rear	Front & Rear
Brightness (nits)	4000	4500
Contrast Ratio	7000:1	7000:1
Lifetime Hours ≥	100,000	100,000
Aspect Ratio	1:1	1:1
IP Rating	IP65	IP65
Technical Specifications		
Viewing Angle°	160/120	160/120
Grey Scale (bit)	16	16
Refresh Rate* (Hz)	3840	3840
Working Voltage		
Scan Rate*		
Operating Temperature (°C / °F)		
Colour Temperature (K)		
Operating Humidity (RH)		
Maximum Power Consumption (W/m²) (W/ft²)		
Average Power Consumption (W/m²) (W/ft²)		

For full specifications, contact us at:
sales@theledstudio.com I +44 (0) 20 3832 9500

*All data contained is subject to change based on project requirements.
*Scan Rate and Refresh Rate subject to project specifications.
*GOB is an essential requirement for displays at ground level.
*Average power consumption is subject to display brightness and pixel configuration.